

DECLARATION OF PERFORMANCE

no. POV 6/2022/EN

1. A unique product type identification code: MIRELON[®] STRIP laminated by PET/PETZ
2. Intended use: Thermal insulation product for use as thermal insulation for equipment, buildings and industrial instalations. Suitable for insulation in areas where washability is necessary for hygienic reasons (food plants).
3. Company, contact adress:

Mirel Vratimov a. s.
Mourová 114/7
739 32 Vratimov
4. System of assesment and verification of constancy of performance of construction products
System 3
5. EN 14313:2009+A1:2013, notified body no. 1023 (Institut pro testování a certifikaci a.s., třída Tomáše Bati 299, Louky, 763 02 Zlín) and notified body no. 1390 (Centrum stavebního inženýrství a.s., ul. Pražská 16, 102 00 Praha 10).
6. The declared properties applies to all thermal insulation products MIRELON[®] STRIP laminated by PET/PETZ.

Basic characteristics		Properties				Harmonized technical specification	
Thermal resistance	Coefficient of thermal conductivity W/m.K	°C	λ_D	°C	λ_D	EN 14313:2009+A1:2013	
		-20	0,039	20	0,049		
		0	0,044	50	0,057		
		10	0,046	90	0,069		
	Dimensions and tolerations						
	- strip thickness	2 - 5 mm	+/- 1 mm	20 and 30 mm	+/- 2,5 mm		
		6 - 10 mm	+/- 1,5 mm	> 30	+/- 3,5 mm		
- strip width	15 mm	+/- 2 mm	X	X			
- strip lenght	L +/- 1,5%						
Reaction on fire	Reaction on fire	F-s3, d2					
Thermal resistance stability in aging/degradation	Coefficient of thermal conductivity W/m.K	see table above					
	Dimensions and tolerations	see table above					
	Dimensions stability	3%					
	Characteristic stability	it does not change					
	Lowest operating temperature	-40°C					
Highest operating temperature	90°C						

NPD – no property has been determined

Basic characteristics		Properties	Harmonized technical specification
Thermal resistance stability at high temperature	Characteristic stability	it does not change	EN 14313:2009+A1:2013
	Dimensions stability	3%	
	Highest operating temperature	90°C	
Stability of reaction on fire at high temperature	Characteristic stability	it does not change	
Stability of reaction on fire in aging/degradation	Characteristic stability	it does not change	
Compressive strength	-	NPD	
Water permeability	Water absorption	WS 005 ($W_p \leq 0,05$)	
	Diffusion resistance	NPD	
Water vapor permeability	Water absorption	NPD	
	Diffusion resistance	NPD	
Reelease of corrosive substances	Trace amounts of soluble ions and pH	CL 5 (≤ 5 mg/kg), PH 6,5	
Sound absorption index	Structure sound transmission	NPD	
	Sound absorption	NPD	
Release of hazardous substances into the internal environment	Release of hazardous substances	NPD	
Burning by incadescent glow	Burning by incadescent glow	NPD	

NPD – no property has been determined

The properties of the above-mentioned product are in accordance with the set of declared properties. This declaration of performance is issued under the sole responsibility of the manufacturer referred to above in accordance with Regulation (EU) No. 305/2011.

In Vratimov, 25. 5. 2022



Ing. Milan Rafaj
Board member
Mirel Vratimov a.s.

Mirel Vratimov a.s.
Mourová 114/7
739 32 Vratimov
IČ: 25912020 • DIČ: CZ25912020
Tel: 596 732 673 • Fax: 596 732 693